



RF rfid ISO-18000-6B ISO-18000-6C UHF
 IP67 EPC G2
 LED SDK
 (C# C++ JAVA)

- ✓ 9 24V
- ✓
- ✓ RF ADC
- ✓ 26dbm (41TS)/30dbm 41TR/TA
- ✓
- ✓ STM Cortex-M3 CPU
- ✓R



✓

✓ UHF

1-5

Impinj E41b

C2336641TR(Indy R2000 VM-64
C2336641TA(Indy R2000 VM-64+
C2336641TS(VM-5S PHYCHIPS PR9200
UHF RFID	
	902 928MHz 865 868MHz
	7dbi
	EPCglobal UHF Class 1 Gen 2 / ISO 18000-6C
	26dbm (41TS) 30dbm 41TR/TA
	1dBm (VANCH
	1-5 >50cm Impinj E41b
	50 /
	FCC Part 15
	ETSI EN 302 308
Cpu	ARM STM32F107 Cortex-M3
	RJ45 RS485 RS232, WIFI 4G GPS
	Bluetooth 4.2
Wi Fi	IEEE802.11b/g/n
	9600 115200bps
RJ45	10Mbps
GPI O	2 1
	Windows Android API
	LED
	<10W
	220V 9V/3A
	5%RH 95%RH()
	IP65



7dbi
C236641

	-20° C +60° C
	-25° C +70° C
	1.2m/6.56ft
	217()*217()*70()mm
	2500g
	ABS+PC